



ThyssenKrupp GfT Tiefbautechnik

Antriebsaggregat power pack MS-A 370 / 420 (V)*	TA 0865 Dat.: 08.10.2002 Name: Spohr
---	---

Technische Daten / Technical Dates:

Dieselmotor / diesel engine:

Leistung / performance:	365/420 [kW]
Drehzahl / speed:	2100 [1/min]
Verteilergetriebe / distributor gear	i=0.704
Dieseltank / fuel tank: Max. Volume	730 [Ltr.]
Hydrauliktank / hydraulic tank: Max. Volume	280 [Ltr.]
Gewicht / Weight(ohne Treibstoff/without fuel):	6.1 [t]

Pumpenausüstung / pump equipment:

Vibr.- Antriebspumpen / drive pump	2 x 130 [cm ³ /U]
Fördermenge / delivery	Max.2 x 370 =740 [L/min]
Arbeitsdruck / working pressure Max.	380 [bar]
Spannhydraulikpumpe / clamping hydraulic pump	10 [cm ³ /U]
Fördermenge / delivery	28 [L/min]
Arbeitsdruck / working pressure Max.	350 [bar]
Hyd.- Ölkühler / - oil cooler	55 [kW]
Vib. - Ölkühler / - oil cooler	** [kW]

* = optional mit Amplitudenverstellung / optional with amplitude adjustment

** =optional vom Vibrator abhängig / optional dependent on vibrator

L	B	H	
4100	1700	2435	[mm]

Subject to Technical modifications

Distributed in Australia & New Zealand by ThyssenKrupp Steelcom <small>A company of ThyssenKrupp Services</small>		ThyssenKrupp
PO Box 840 North Sydney NSW 2059 Australia T: +61 2 9954 9166 Sales +61 2 4966 0688 F: +61 2 9955 4298 enquiries@steelcom.com.au www.steelcom.com.au	PO Box 51254 Pakuranga Auckland 2140 New Zealand T: +64 9 576 3977 F: +64 9 576 3978 afenn@steelcomnz.co.nz www.steelcomnz.co.nz	