



ThyssenKrupp GfT Tiefbautechnik

Antriebsaggregat power pack MS-A 180 (V)*	TA 0923 Dat.: 06.02.2003 Name: Kraeling
---	--

Technische Daten / Technical Dates:

Dieselmotor / diesel engine:

Leistung / performance: 187 [kW]
 Drehzahl / speed: 2500 [1/min]

Dieseltank / fuel tank: Max. Volume 550 [Ltr.]

Hydrauliktank / hydraulic tank: Max. Volume 250 [Ltr.]

Gewicht / Weight(ohne Treibstoff/without fuel): ca. 4.5 [t]

Pumpenausstattung / pump equipment:

Vibr.- Antriebspumpen / drive pump 1 x 130 [cm³/U]

Fördermenge / delivery 310 [L/min]

Arbeitsdruck / working pressure Max. 380 [bar]

Spannhydraulikpumpe / clamping hydraulic pump 10 [cm³/U]

Fördermenge / delivery 25 [L/min]

Arbeitsdruck / working pressure Max. 350 [bar]

Hyd.- Ölkühler / - oil cooler 30 [kW]

Vib. - Ölkühler / - oil cooler ** [kW]

* = optional mit Amplitudenverstellung / optional with amplitude adjustment

** = optional vom Vibrator abhängig / optional dependent on vibrator

L	B	H	
3700	1490	2300	[mm]
145.7	58.7	90.6	[inch]

Subject to Technical modifications

Distributed in Australia & New Zealand by ThyssenKrupp Steelcom A company of ThyssenKrupp Services		ThyssenKrupp
PO Box 840 North Sydney NSW 2059 Australia T: + 61 2 9954 9166 Sales + 61 2 4966 0688 F: + 61 2 9955 4298 enquiries@steelcom.com.au www.steelcom.com.au	PO Box 51254 Pakuranga Auckland 2140 New Zealand T: + 64 9 576 3977 F: + 64 9 576 3978 afenn@steelcomnz.co.nz www.steelcomnz.co.nz	